RAPIDLY DEPLOY FIBER WITH PRE-LOADED ENCLOSURES



Experience the ultimate in fiber connectivity with **TheNID[™]** with **Reel**, featuring a preloaded rotating slack storage reel and versatile cable entry system. Eliminate in-field splicing, reduce installation time, and ensure reliable performance in any environment.

FEATURES

- Preloaded Rotating Slack Storage Reel: Comes with 50, 100, or 150 ft of micro armored pushable fiber, eliminating the need for in-field splicing.
- Versatile Cable Entry System: Accommodates both round and flat drop cables with a variable clamp entry.
- **High-Impact Thermoplastic Housing:** Durable construction for protection against environmental factors.
- Secure Closure: Closes with a 3/8" hex bolt and provision for a security seal.
- Integrated Copper Ground Lug: Provides a reliable grounding point for added safety.
- **Compliance and Environmental Rating:** GR-771 rated and RoHS compliant for safety and environmental protection.

MODELS

FPP-TN-C3-SAB-NKHI3-050F 50 ft micro-armored pushable fiber

FPP-TN-C3-SAB-NKHI3-100F 100 ft micro-armored pushable fiber

FPP-TN-C3-SAB-NKHI3-150F 150 ft micro-armored pushable fiber

All Models Feature

- SC/APC
- Simplex adapter
- Supports round and flat cable
- Pre-installed ground lug

LYNN_NIDRArm_SellSheet.pdf

Up to 1-inch conduit

240614

CONTACT

NSI