

# MiniFort Enclosures

Feature for feature, the MiniFort is the lowest priced outdoor rack mount enclosure available. Pole, ground or wall mountable, the compact light-weight MiniFort can be deployed with minimal cost for virtually any application.





**Commonly Used For:** • Cellular Backhaul • Fiber Termination  
 • Repeating / Splitting Fiber to MDU • Business Services  
 • Power Systems • Battery Storage • Security and Surveillance

**Standard features:**



**.090" AL.** High strength to weight ratio.



**Ground Bar**  
5-Position aluminum ground bar



**Protection**  
This enclosure protects against rain, sleet, snow, splashing water and damage from external ice formation.



**20 Amp**  
Quad Receptacle.



**All stainless hardware**



**High security**  
1/4 Turn padlockable compression locks




**Rack Size:** 19" EIA, adjustable

**Finish** Enclosures are finished to the current Telcordia standards.



## MiniFort Series Configuration


**9RU**



P/N: AM-202418-9RU\*\*

\*Basic Weight: 35 lbs


**16RU**



P/N: AM-322418-16RU\*\*

\*Basic Weight: 55 lbs

**24RU**



P/N: AM-462418-24RU\*\*

\*Basic Weight: 75 lbs

\*Weight without options. Shipping weights will vary. \*\*When ordering MiniForts with fan option add "-F" to the end of the part number.

## MiniFort Mounting Options

**Ground Pad Mount**  
P/N: AM-62418-GM

6" Flanged base with mounting holes. Front & back removeable panels




**Pole Mount Bracket**

P/N: AM-2418-PM  
Bracket for use with mounting clamps, straps or lag bolts. Compatible with 4"-8" diameter poles.



**Wall Mount Bracket**  
P/N: AM-2418-WM

Flanged back panels with mounting holes.



## MiniFort Options For additional options see our website. [www.amprod.us](http://www.amprod.us)



**AC 1000 BTU/hr**

P/N: AMMF-AC1000-115  
With heater.



**Heater**  
Call for P/N's

With thermostat included.



**AC 2000 BTU/hr & Heat**

P/N: AMMF-AC2000-115\*  
With heater.

\*For use on 32" and 46" models only.

**Ground Bar**

P/N: AM-2X6-GB  
Copper ground bar - isolated.

**Storage Box**

P/N: AM-2418-BB  
16" tall, ventilated storage enclosure. Single door, padlockable, 1/4 turn latches.



**Fan P/Ns:**  
AM-2418-FP-115  
AM-2418-FP-48  
AM-2418-FP-24  
AM-2418-FP-12

115VAC /12, 24 or 48VDC. Adjustable thermostat is included.



**Insulation**

Call for P/N's  
Recommended for all climate control options.

**Equipment Tray**

P/N: AM-2418-BT  
May require second set of rack rails.

**Latch Tool**

P/N: AM-CWTOOL



**Door Alarm**

P/N: AM-2418-DLRM

**Additional Set of Rails**

P/Ns: AM-202418-RR  
AM-322418-RR  
AM-462418-RR

2nd set of rack rails for battery tray installation.

**Wood Back Panel**

P/Ns: AM-202418-WB  
AM-322418-WB  
AM-462418-WB

3/4" Plywood bolted to back wall of enclosure.